

DESIGN DATA

TANK CONTENTS		S.G. 1.5
DESIGN PRESSURE: ATMOSPHERIC	MAXIMUM CAPACITY (LTRS):	
DESIGN TEMPERATURE: 40°C	WORKING CAPACITY (LTRS):	
WORKING PRESSURE: ATMOSPHERIC	APPROX. WEIGHT FULL (KGS):	
WORKING TEMPERATURE: 40°C	APPROX. WEIGHT EMPTY (KGS):	
MOULDED LIFTING LUGS: 4 - 0°, 90°, 180° & 270°		
METHOD OF SUPPORT: FIRM, FLAT, FULLY SUPPORTING BASE OF CONCRETE OR OTHER SUITABLE MATEREAL		

MATERIAL DATA

MATERIALS OF CONSTRUCTION:	COLOUR - Black
MATRIX REVOLVE N-307. REVOLVE IS A HIGH DENSITY (0.939 g/cm3), LOW MELT (3.5 g/ 10 min) HEXENE POLYETHYLENE GRADE FOR ROTOMOULDING. THE GRADE IS FULLY PROTECTED AGAINST THERMAL AND LIGHT DEGRADATION: N-307 IS UV10 STABILISED.	


INSPECTION AND TESTING

WORKS TEST: ALL TANKS ARE THICKNESS TESTED BY ULTRASOUND AFTER DEMOULD IN ADDITION AIR SUPPORTED LEAK TEST ARE CARRIED OUT ON FLANGE LINES.

Notes:

	NAME	SIGNATURE	DATE
DRAWN	LC	L.Crane	17/09/2020
CHECKED	-	-	-
APPROVED	-	-	-

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN MILLIMETERS  
SURFACE FINISH: MDPE  
TOLERANCES: ±3%



3RD ANGLE PROJECTION

DO NOT SCALE DRAWING      REVISION: -

**ENDURAMAXX®**  
FLUID MANAGEMENT INNOVATION

TITLE:  
**1500L-60DEG OT**

DWG NO:      A3

SCALE:1:25      SHEET 1 OF 1